

nerac.com
PEOPLE POWERED SEARCHING

 my account  learning center  patent cart  document ca

home

searching ▾

patents ▾

documents ▾

toc journal watch ▾

Format Examples

US Patent

US6024053 or 6024053

US Design Patent

D0318249

US Plant Patents

PP8901

US Reissue

RE35312

US SIR

H1523

US Patent Applications

20020012233

World Patents

WO04001234 or WO2004012345

European

EP1067252

Great Britain

GB2018332

German

DE29980239

Nerac Document Number (NDN)

certain NDN numbers can be used
for patents

[view examples](#)



6.0 recommended
Win98SE/2000/XP

Patent Ordering

 help

Enter Patent Type and Number: optional reference note

GO

☐ Add patent to cart automatically. If you
uncheck this box then you must *click on*
Publication number and view abstract to Add to
Cart.

0 Patent(s) in Cart

Patent Abstract

 Add to cart

GER 1996-07-11 ~~19505369~~ **Procedure for the
improvement of the function and catalytic activity;
substances during an electro-chemical or
electricalcatalytic process;; working catalytically from
electrodes and**

INVENTOR(S)- Gorris, Rainer 65197 Wiesbaden DE

APPLICANT(S)- Gorris, Rainer 65197 Wiesbaden DE

PATENT NUMBER- 19505369/DE-C1

PATENT APPLICATION NUMBER- 19505369

DATE FILED- 1995-02-17

DOCUMENT TYPE- C1, PATENT SPECIFICATION (FIRST
PUBL.)

PUBLICATION DATE- 1996-07-11

INTERNATIONAL PATENT CLASS- G01N02730;
C25B01502; G01N027406C; G01N027417C

PATENT APPLICATION PRIORITY- 19505369, A

PRIORITY COUNTRY CODE- DE, Germany, Ged. Rep. of

PRIORITY DATE- 1995-02-17

FILING LANGUAGE- German

LANGUAGE- German NDN- 203-0357-5732-7

It becomes a procedure for the conditioning and/or re-
establishment of; the function and catalytic activity of
electrodes (2, 3) and; catalytically working substances
during an electro-chemical or; electricalcatalytic process
described. Runs off under admission or; delivery of electrons
directly or in one or more intermediate steps an; ionization

or a Deionisationsprozesse in a cell, which is formed for; electrolytes (1) or an electrically leading layer from two by from; each other separated electrodes (2, 3) or catalytic coatings, whereby; a tension is applied to the two electrodes (2, 3). With such cells; frequently a decrease of the measuring cell tension occurs after; longer period of use, which leads to the incorrect announcement of to; high oxygen values. Furthermore the inertness with sinking temperature; increases strongly. In order to reach that the function and catalytic; effect of such messzellen are improved, without interrupting or affect; thereby the measuring enterprise excessively to for a long time, it; plans the invention that the tension set on the electrodes (2, 3) is; at least once commutated.

EXEMPLARY CLAIMS- 1. Procedure for the conditioning and/or re-establishment of the function and catalytic activity by electrodes (2,3) and catalytically working substances (5, 6) during an electro-chemical or electricalcatalytic process, with which under admission or delivery of electrons directly or during one or more intermediate steps a process runs off of the ionization or Deionisation, by a cell, which is formed for electrolytes (1) from two by or an electrically leading layer (9) from each other separate electrodes (2,3) or catalytic coatings (5,6) and with that a tension to the two electrodes (2, 3) or catalytic coatings (5,6) it is put on by the fact characterized that the direction of the tension at least once one commutates. 2. Procedure according to requirement 1, by it characterized that the tension is an alternating voltage, their process rectangular (10), trapezoidally (11), like saw teeth or sinusoidal (12) is. 3. Procedure according to requirement 1 or 2, by the fact characterized that the tension put on is larger than the strength by electric motors, which can occur at the cell. 4. Procedure according to requirement 1, 2 or 3, by the fact characterized that the pole reversal frequency lies in the low frequency range. 5. Procedure after one of the requirements 1 to 4, by the fact characterized that the height of the tensions is kept alike. 6. Procedure after one of the requirements 1 to 5, by the fact characterized that the duration of the positive and the negative tension sections is kept alike. 7. Procedure after one of the requirements 1 to 6, by the fact characterized that after completion of the tension combination the two electrodes (2,3; 7,8) of the cell to be short circuit.

NO-DESCRIPTORS

Nerac, Inc. One Technology Drive . Tolland, CT

Phone (860) 872-7000 Fax (860) 875-1749

©1995-2003 All Rights Reserved . [Privacy Statement](#) . [Report a Problem](#)